



**LOAD DATA**  
 Bullet Brand: Federal®  
 6.5MM  
 Weight / Type: 140gr Fusion®

More reloading data can be found at [federalpremium.com](http://federalpremium.com)

**6.5 CREEDMOOR Test Firearm: 24" test barrel \*note: Compressed**

POWDER	OAL (IN.)	PRIMER	BRASS	Starting Load		Max Load	
				CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloder® 26	2.750	Fed 210	Fed	40.3	2539	44.8	2752
Alliant Reloder® 19	2.750	Fed 210	Fed	40.1	2579	43.3*	2731
Alliant Power Pro™ 4000-MR	2.750	Fed 210	Fed	38.1	2507	42.2	2728
Alliant Reloder® 22	2.750	Fed 210	Fed	40.6	2625	43.0*	2723
Alliant Reloder® 17	2.750	Fed 210	Fed	35.9	2498	39.8	2714
Alliant Reloder® 23	2.750	Fed 210	Fed	38.1	2523	42.2*	2707
Alliant Reloder® 16	2.750	Fed 210	Fed	35.5	2476	39.4	2660

**260 REMINGTON Test Firearm: 24" test barrel \*note: Compressed**

POWDER	OAL (IN.)	PRIMER	BRASS	Starting Load		Max Load	
				CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloder® 26	2.700	Fed 210	Fed	42.6	2493	47.1*	2783
Alliant Reloder® 22	2.700	Fed 210	Fed	41.3	2531	45.7*	2774
Alliant Power Pro™ 4000-MR	2.700	Fed 210	Fed	40.2	2507	44.4*	2769
Alliant Reloder® 19	2.700	Fed 210	Fed	41.0	2517	45.4*	2761
Alliant Reloder® 17	2.700	Fed 210	Fed	37.5	2493	41.6	2742
Alliant Reloder® 23	2.700	Fed 210	Fed	40.3	2507	44.7*	2738
Alliant Reloder® 16	2.700	Fed 210	Fed	37.9	2499	42.0*	2723