

## LOAD DATA

Bullet Brand: Federal®  
 270 Cal Weight/Type: 136gr Edge TLR®  
 More reloading data can be found at federalpremium.com

### 270 Winchester 24" SAAMI chamber Universal Receiver test barrel

POWDER	OAL (IN)	PRIMER	BRASS	Starting Load		Max Load	
				CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloader® 17	3.255	Fed 210	Fed	49.3	2819	54.6	3131
Alliant Power Pro™ 4000-MR	3.255	Fed 210	Fed	52.5	2837	58.2**	3127
Alliant Reloader® 16	3.255	Fed 210	Fed	50.5	2851	56.0**	3122
Alliant Reloader® 26	3.255	Fed 210	Fed	55.9	2826	60.0**	3076
Alliant Reloader® 19	3.255	Fed 210	Fed	54.2	2825	59.0**	3067
Alliant Reloader® 23	3.255	Fed 210	Fed	52.8	2831	57.0**	3044
Alliant Reloader® 22	3.255	Fed 210	Fed	53.8	2816	58.0**	3032

### 270 Winchester Short Magnum 24" SAAMI chamber Universal Receiver test barrel

POWDER	OAL (IN)	PRIMER	BRASS	Starting Load		Max Load	
				CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloader® 26	2.860	Fed 215	Fed	60.8	2947	67.7**	3270
Alliant Reloader® 17	2.860	Fed 215	Fed	55.2	3028	61.1	3259
Alliant Power Pro™ 4000-MR	2.860	Fed 215	Fed	58.4	2961	64.6	3251
Alliant Reloader® 22	2.860	Fed 215	Fed	58.5	3007	64.9**	3229
Alliant Reloader® 23	2.860	Fed 215	Fed	58.4	3000	64.3**	3225
Alliant Reloader® 19	2.860	Fed 215	Fed	58.0	2983	64.7	3222
Alliant Reloader® 16	2.860	Fed 215	Fed	55.2	2948	61.6	3203

### 270 Weatherby Magnum 24" SAAMI chamber Universal Receiver test barrel

POWDER	OAL (IN)	PRIMER	BRASS	Starting Load		Max Load	
				CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloader® 26	3.285	Fed 215	Fed	64.0	2853	70.3	3207
Alliant Reloader® 25	3.285	Fed 215	Fed	64.9	2843	71.9	3162
Alliant Reloader® 23	3.285	Fed 215	Fed	58.9	2866	65.4	3156
Alliant Reloader® 22	3.285	Fed 215	Fed	61.0	2859	67.6	3155

\*\*Compressed