

## LOAD DATA

Bullet Brand: Federal®  
308 Cal. Weight/Type: 200gr Edge TLR®

More reloading data can be found at federalpremium.com

### 30-06 Springfield 24" SAAMI chamber Universal Receiver test barrel

POWDER	OAL (IN)	PRIMER	BRASS	Starting Load		Max Load	
				CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Power Pro™ 4000-MR	3.290	Fed 210	Fed	49.2**	2413	54.8**	2635
Alliant Reloader® 16	3.290	Fed 210	Fed	47.3**	2395	52.7**	2627
Alliant Reloader® 26	3.290	Fed 210	Fed	51.8**	2333	57.5**	2588
Alliant Reloader® 17	3.290	Fed 210	Fed	44.7	2352	49.7**	2579
Alliant Reloader® 19	3.290	Fed 210	Fed	49.2**	2358	54.5**	2567

### 300 Winchester Magnum 24" SAAMI chamber Universal Receiver test barrel

POWDER	OAL (IN)	PRIMER	BRASS	Starting Load		Max Load	
				CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Power Pro™ 4000-MR	3.470*	Fed 215	Fed	63.2**	2522	70.8**	2849
Alliant Reloader® 26	3.470*	Fed 215	Fed	67.7**	2544	74.0**	2849
Alliant Reloader® 22	3.470*	Fed 215	Fed	65.4**	2499	72.0**	2789
Alliant Reloader® 23	3.470*	Fed 215	Fed	67.0**	2553	70.0**	2701
Alliant Reloader® 19	3.470*	Fed 215	Fed	67.8**	2550	70.8**	2692
Alliant Reloader® 25	3.470*	Fed 215	Fed	71.5**	2488	73.0**	2585

### 300 Winchester Magnum 24" SAAMI chamber Universal Receiver test barrel

POWDER	OAL (IN)	PRIMER	BRASS	Starting Load		Max Load	
				CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloader® 26	2.850	Fed 215	Fed	63.0**	2604	69.5**	2890
Alliant Reloader® 22	2.850	Fed 215	Fed	60.6**	2592	67.0**	2876
Alliant Power Pro™ 4000-MR	2.850	Fed 215	Fed	60.0**	2610	66.3**	2873
Alliant Reloader® 16	2.850	Fed 215	Fed	57.5**	2589	63.7**	2837
Alliant Reloader® 19	2.850	Fed 215	Fed	62.0**	2602	67.0**	2826
Alliant Reloader® 17	2.850	Fed 215	Fed	54.5	2559	60.4**	2822

### 300 Remington Ultra Magnum 24" SAAMI chamber Universal Receiver test barrel

POWDER	OAL (IN)	PRIMER	BRASS	Starting Load		Max Load	
				CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloader® 25	3.700*	Fed 215	Fed	80.0	27.57	88.6	2997
Alliant Reloader® 26	3.700*	Fed 215	Fed	78.3	2691	86.9	2995
Alliant Reloader® 23	3.700*	Fed 215	Fed	76.6	2739	84.9	2967
Alliant Reloader® 22	3.700*	Fed 215	Fed	74.2	2728	82.5	2959
Alliant Reloader® 19	3.700*	Fed 215	Fed	74.9	2745	83.0	2954
Alliant Power Pro™ 4000-MR	3.700*	Fed 215	Fed	74.2	2692	82.4	2954

### 300 Weatherby Magnum 24" SAAMI chamber Universal Receiver test barrel

POWDER	OAL (IN)	PRIMER	BRASS	Starting Load		Max Load	
				CHARGE WT (GR)	VELOCITY (FT/SEC)	CHARGE WT (GR)	VELOCITY (FT/SEC)
Alliant Reloader® 26	3.560	Fed 215	Fed	72.6	2689	80.7**	3012
Alliant Reloader® 25	3.560	Fed 215	Fed	76.1	2690	84.5**	2969
Alliant Reloader® 23	3.560	Fed 215	Fed	71.7	2700	79.3**	2963
Alliant Reloader® 19	3.560	Fed 215	Fed	71.4**	2657	79.4**	2945
Alliant Reloader® 22	3.560	Fed 215	Fed	69.7	2637	77.4**	2924
Alliant Power Pro™ 4000-MR	3.560	Fed 215	Fed	69.2	2658	76.7**	2923
Alliant Reloader® 33	3.560	Fed 215	Fed	82.7**	2568	91.7**	2904

\*COAL greater than SAAMI max OAL \*\*Compressed