

HANDGUN BALLISTICS

Abbreviation Key: BTHP = boat-tail hollow point; BTSP = boat-tail soft point; FN = flat nose; LRN = lead round nose; LSW = lead semi-wadcutter; LW = lead wadcutter; SWC = semi-wadcutter; SWHP = semi-wadcutter hollow point; CB = conical ball reduced power/noise; FP = flat point; CP = copper-plated; L = lead; J = jacketed; HP = hollow-point; RN = round nose; SHP = segmented hollow-point; SP = soft point; FMJ = full metal jacket; TSJ = total synthetic jacket; TMF = toxic-metal-free; TMJ = totally encapsulated bullet; V = vented barrel; HE = high energy (not for use in semi-automatic rifles); † = not for revolvers; ◊ = nickel-plated case; RMEF = a portion of the proceeds from the sale of this product is donated to Rocky Mountain Elk Foundation; SQ = a portion of the proceeds from the sale of this product is donated to Safari Club International; CLM = cartridge length longer than SAAMI max, may not fit in all magazines; *Molycoat: molybdenum disulfide dry film lubricant

Federal Premium® Handgun

USAGE	FEDERAL LOAD NO.	CALIBER	BULLET WEIGHT IN		BULLET STYLE	VELOCITY IN FEET PER SECOND (TO NEAREST 10 FPS)					ENERGY IN FOOT-POUNDS (TO NEAREST 5 FOOT-POUNDS)				TRAJECTORY 9 INCHES ABOVE BORE LINE				TEST BARREL LENGTH INCHES	
			GRAINS	GRAMS		MUZZLE	25 YDS.	50 YDS.	75 YDS.	100 YDS.	MUZZLE	25 YDS.	50 YDS.	75 YDS.	100 YDS.	25 YDS.	50 YDS.	75 YDS.		100 YDS.
FEDERAL PREMIUM PERSONAL DEFENSE HST®																				
6	P9HST1S	9MM LUGER	124	8.04	HST	1150	1095	1049	1010	977	364	330	303	281	263	⊕	-0.9	-3.8	-8.8	4
6	P9HST2S	9MM LUGER	147	8.04	HST	1000	976	953	933	914	326	311	297	284	273	⊕	-1.4	-5.2	-11.5	4
6	P40HST1S	40 S&W	180	11.66	HST	1010	980	954	930	908	408	384	364	346	329	⊕	-1.4	-5.1	-11.4	4
6	P10HST1S	10MM AUTO	200	12.96	HST	1130	1051	991	943	902	567	490	436	395	361	⊕	-1.1	-4.3	-10	5
6	P45HST2S	45 AUTO	230	14.9	HST	890	872	856	840	824	404	389	374	360	347	⊕	-2.0	-6.9	-15.0	5
FEDERAL PREMIUM PERSONAL DEFENSE HST MICRO																				
6	P380HST1S	380 AUTO	99	6.42	HST	1030	986	948	915	885	233	213	197	184	172	⊕	-1.3	-5.1	-11.4	3.75
6	P38HST1S	38 SPECIAL +P	130	8.42	HST	890	866	844	823	803	229	217	206	196	186	⊕	-2.0	-7.1	-15.3	4-V
6	P9HST5S	9MM LUGER	150	9.72	HST	900	883	866	851	836	270	260	250	241	233	⊕	-1.9	-6.7	-14.5	4
FEDERAL PREMIUM PERSONAL DEFENSE HYDRA-SHOK DEEP®																				
6	P380HSD1	380 AUTO	99	6.42	HYDRA-SHOK DEEP	1000	949	907	869	835	220	198	181	166	153	⊕	-1.5	-5.7	-12.7	3.75
6	P9HSD1	9MM LUGER	135	8.75	HYDRA-SHOK DEEP	1060	1026	996	970	946	337	316	298	282	268	⊕	-1.2	-4.5	-10.2	4
6	P40HSD1	40 S&W	165	10.69	HYDRA-SHOK DEEP	100	1011	978	949	922	404	375	350	330	311	⊕	-1.2	-4.7	-10.6	4
6	P45HSD1	45 AUTO	210	13.61	HYDRA-SHOK DEEP	980	952	927	903	882	448	423	400	381	363	⊕	-1.5	-5.5	-12.2	5
FEDERAL PREMIUM PERSONAL DEFENSE® HYDRA-SHOK®																				
6	P32HS1	32 AUTO	65	4.21	HYDRA-SHOK	925	892	862	834	808	123	115	107	100	94	⊕	-1.8	-6.6	-14.5	4
6	P9HS1	9MM LUGER	124	8.04	HYDRA-SHOK	1120	1070	1028	993	961	345	315	291	271	255	⊕	-1.0	-4.0	-9.3	4
6	P9HS2	9MM LUGER	147	9.53	HYDRA-SHOK	1000	976	953	933	914	326	311	297	284	273	⊕	-1.4	-5.2	-11.5	4
6	P357S1	357 SIG	125	8.1	HYDRA-SHOK	1350	1266	1192	1130	1078	506	445	395	354	323	⊕	-0.5	-2.4	-6.1	4
6	P38HS1	38 SPECIAL +P	129	8.36	HYDRA-SHOK	950	926	904	884	865	258	246	234	224	214	⊕	-1.6	-5.9	-13	4-V
6	P357HS1	357 MAGNUM	158	10.24	HYDRA-SHOK	1240	1187	1139	1098	1063	539	494	455	423	396	⊕	-0.6	-3.0	-7.1	4-V
6	P40HS2	40 S&W	155	10.04	HYDRA-SHOK	1140	1079	1030	989	954	447	401	365	337	313	⊕	-1.0	-4.0	-9.2	4
6	P40HS3	40 S&W	165	10.69	HYDRA-SHOK	980	950	924	899	876	352	331	312	296	281	⊕	-1.5	-5.6	-12.3	4
6	P40HS1	40 S&W	180	11.66	HYDRA-SHOK	1000	972	946	923	901	400	377	358	340	324	⊕	-1.4	-5.3	-11.6	4
6	P10HS1	10MM AUTO	180	11.66	HYDRA-SHOK	1030	998	970	945	921	424	398	376	357	339	⊕	-1.3	-4.9	-10.9	5
6	P44HS1	44 REM. MAGNUM	240	15.55	HYDRA-SHOK	1210	1152	1102	1060	1024	780	707	647	599	559	⊕	-0.7	-3.3	-7.7	4-V
6	P45HS1	45 AUTO	230	14.9	HYDRA-SHOK	900	882	865	848	832	414	397	382	367	354	⊕	-1.9	-6.7	-14.6	5
FEDERAL PREMIUM PERSONAL DEFENSE HYDRA-SHOK LOW-RECOIL																				
6	PD327HS1 H	327 FEDERAL MAGNUM	85	5.51	HYDRA-SHOK	1400	1306	1221	1150	1091	370	322	281	250	225	⊕	-0.4	-2.2	-5.7	4-V
6	PD380HS1 H	380 AUTO	90	5.83	HYDRA-SHOK	1000	953	914	879	847	200	182	167	154	143	⊕	-1.5	-5.6	-12.5	3.75
6	PD9HS5 H	9MM LUGER	135	8.75	HYDRA-SHOK	1060	1026	996	970	946	337	316	298	282	268	⊕	-1.2	-4.5	-10.2	4
6	PD38HS3 H	38 SPECIAL	110	7.13	HYDRA-SHOK	980	943	911	882	855	235	217	203	190	179	⊕	-1.5	-5.7	-12.6	4-V
6	PD357HS2 H	357 MAGNUM	130	8.42	HYDRA-SHOK	1410	1331	1258	1193	1138	574	511	457	411	373	⊕	-0.3	-2.0	-5.2	4-V
6	PD40HS4 H	40 S&W	135	8.75	HYDRA-SHOK	1200	1116	1051	999	957	432	373	331	299	274	⊕	-0.8	-3.7	-8.6	4
6	PD45HS3 H	45 AUTO	165	10.69	HYDRA-SHOK	1060	1014	976	942	912	412	377	349	325	305	⊕	-1.2	-4.7	-10.6	5
FEDERAL PREMIUM PUNCH™																				
6	PD380P1	380 AUTO	85	5.51	JHP	1000	949	907	869	835	189	170	155	143	132	⊕	-1.5	-5.7	-12.7	3.75
6	PD38P1	38 SPECIAL +P	120	7.78	JHP	1000	949	907	869	835	266	240	219	201	186	⊕	-1.5	-5.7	-12.7	4-V
6	PD40P1	40 S&W	165	10.69	JHP	1130	1078	1035	999	967	468	426	392	365	342	⊕	-1	-4	-9.1	4
6	PD45P1	45 AUTO	230	14.9	JHP	890	872	856	840	824	404	389	374	360	347	⊕	-2	-6.9	-15	5
6	PD9P1	9MM LUGER	124	8.04	JHP	1150	1095	1049	1010	977	364	330	303	281	263	⊕	-0.9	-3.8	-8.8	4
FEDERAL PREMIUM HUNTING HANDGUN																				
2	P357SA	357 MAGNUM	180	11.66	SWIFT A-FRAME	1130	1086	1049	1016	988	510	471	439	413	390	⊕	-0.9	-3.9	-8.9	6-V
2	P41SA	41 REM. MAGNUM	210	13.61	SWIFT A-FRAME	1360	1289	1224	1167	1118	862	775	698	635	582	⊕	-0.4	-2.3	-5.7	6-V
2	P44SA	44 REM. MAGNUM	280	18.14	SWIFT A-FRAME	1170	1107	1056	1013	977	851	762	693	638	594	⊕	-0.9	-3.7	-8.6	6-V
2	P454SA	454 CASULL	300	19.44	SWIFT A-FRAME	1520	1410	1311	1223	1149	1539	1324	1145	996	879	⊕	-0.2	-1.7	-4.6	5.7-V
2	P460SA	460 S&W	300	19.44	SWIFT A-FRAME	1750	1625	1506	1397	1300	2040	1758	1510	1300	1125	⊕	0.1	-0.8	-2.8	8.4-V
3	P500SA	500 S&W	325	21.06	SWIFT A-FRAME	1800	1677	1559	1449	1350	2338	2028	1754	1515	1315	⊕	0.1	-0.6	-2.4	8.4-V
3	P10T1	10MM AUTO	180	11.66	TROPHY BONDED JSP	1275	1192	1123	1067	1021	650	568	504	455	417	⊕	-0.6	-3.0	-7.2	5
2	P357XB1	357 MAGNUM	140	9.07	BARNES EXPANDER	1400	1326	1257	1196	1143	609	546	491	445	406	⊕	-0.3	-2.0	-5.3	6-V
2	P41XB1	41 REM. MAGNUM	180	11.66	BARNES EXPANDER	1340	1262	1193	1134	1084	718	636	569	514	470	⊕	-0.5	-2.5	-6.1	6-V
2	P44XB1	44 REM. MAGNUM	225	14.58	BARNES EXPANDER	1280	1209	1147	1096	1052	818	730	658	600	553	⊕	-0.6	-2.8	-6.9	6-V
2	P454XB1	454 CASULL	250	16.2	BARNES EXPANDER	1530	1423	1326	1239	1165	1299	1123	976	852	753	⊕	-0.2	-1.6	-4.4	5.7-V
2	P460XB1	460 S&W	275	17.82	BARNES EXPANDER	1670	1595	1522	1453	1388	1703	1553	1415	1289	1177	⊕	0.1	-0.8	-2.7	8.4-V
2	P500XB1	500 S&W	275	17.82	BARNES EXPANDER	1660	1544	1435	1337	1249	1682	1455	1257	1091	952	⊕	0.0	-1.1	-3.4	8.4-V
FEDERAL PREMIUM GOLD MEDAL®																				
7	GM38A	38 SPECIAL	148	9.59	LW MATCH	690	650	610	570	540	155	140	120	110	95	⊕	-4.3	-14.4	-31.2	4-V
7	GM45B	45 AUTO	185	11.99	FMJ-SWC MATCH	770	740	700	670	640	245	220	205	185	170	⊕	-3.1	-10.6	-23.0	5
7	GM45A	45 AUTO	230	14.90	FMJ MATCH	860	840	830	810	800	380	365	350	340	325	⊕	-2.2	-7.5	-16.1	5

Federal® Handgun

USAGE	FEDERAL LOAD NO.	CALIBER	BULLET WEIGHT IN		BULLET STYLE	VELOCITY IN FEET PER SECOND (TO NEAREST 5 FPS)					ENERGY IN FOOT-POUNDS (TO NEAREST 5 FOOT-POUNDS)			
-------	------------------	---------	------------------	--	--------------	--	--	--	--	--	---	--	--	--

Usage Key: 1 = Varmints, predators, small game; 2 = medium game; 3 = large, heavy game; 4 = dangerous game; 5 = target shooting, training, practice; 6 = self defense; 7 = competition shooting; 8 = pest control; 9 = low noise, training, specialty.

These trajectory tables were calculated by computer using the best available data for each load. Trajectories are representative of the nominal behavior of each load at standard conditions (59°F temperature; barometric pressure of 29.53 inches; altitude at sea level). Shooters are cautioned that actual trajectories may differ due to variations in altitude, atmospheric conditions, guns, sights and ammunition.

Syntech® Handgun

USAGE	FEDERAL LOAD NO.	CALIBER	BULLET WEIGHT IN		BULLET STYLE	VELOCITY IN FEET PER SECOND (TO NEAREST 10 FPS)					ENERGY IN FOOT-POUNDS (TO NEAREST 5 FOOT-POUNDS)					TRAJECTORY .9 INCHES ABOVE BORE LINE				TEST BARREL LENGTH INCHES
			GRAINS	GRAMS		MUZZLE	25 YDS.	50 YDS.	75 YDS.	100 YDS.	MUZZLE	25 YDS.	50 YDS.	75 YDS.	100 YDS.	25 YDS.	50 YDS.	75 YDS.	100 YDS.	
SYNTECH RANGE™																				
5	AE9SJ1	9MM LUGER	115	7.45	TSJ	1130	1105	1083	1062	1043	326	312	299	288	278	⊕	-0.9	-3.6	-8.3	4
5	AE9SJ2	9MM LUGER	124	8.04	TSJ	1050	1011	978	949	922	304	282	263	248	234	⊕	-1.2	-4.7	-10.6	4
5	AE40SJ1	40 S&W	165	10.69	TSJ FP	1050	1027	1007	988	970	404	387	371	357	345	⊕	-1.2	-4.4	-10.0	4
5	AE45SJ1	45 AUTO	230	14.9	TSJ	830	821	812	803	795	352	344	337	329	322	⊕	-2.3	-7.9	-16.8	5
SYNTECH ACTION PISTOL™																				
5	AE9SJAP1	9MM LUGER	150	9.72	TSJ	870	854	839	824	810	252	243	234	226	219	⊕	-2.1	-7.3	-15.6	4
5	AE40SJAP1	40 S&W	205	13.28	TSJ	830	813	797	782	767	314	301	289	278	267	⊕	-2.4	-8.1	-17.5	4
5	AE45SJAP1	45 AUTO	220	14.26	STJ	810	795	780	766	752	320	309	297	287	277	⊕	-2.5	-8.6	-18.5	5
SYNTECH PCC™																				
5	AE9SJPC1	9MM LUGER	130	8.42	STJ	1130	1078	1035	999	967	369	336	309	288	270	⊕	-1	-4	-9.1	16
SYNTECH TRAINING MATCH®																				
5	AE9SJ4	9MM LUGER	124	8.04	TSJ	1150	1064	1000	949	907	364	312	275	248	226	⊕	-1	-4.2	-9.8	4
5	AE9SJPC1	9MM LUGER	130	8.42	TSJ	1130	1078	1035	999	967	369	336	309	288	270	⊕	-1	-4	-9.1	16
5	AE9SJ3	9MM LUGER	147	9.53	STJ	1000	976	953	933	914	326	311	297	284	273	⊕	-1.4	-5.2	-11.5	4
5	AE40SJ2	40 S&W	180	11.66	TSJ	1010	958	914	876	842	408	367	334	307	283	⊕	-1.5	-5.5	-12.4	4
5	AE45SJ2	45 AUTO	230	14.9	TSJ	890	855	824	794	767	404	374	346	322	300	⊕	-2.1	-7.3	-16	5
SYNTECH DEFENSE™																				
6	S9SJT1	9MM LUGER (9X19MM PARABELLUM)	138	8.94	STJ	1050	989	940	899	862	338	300	271	248	228	⊕	-1.3	-5.1	-11.5	4
6	S40SJT1	40 S&W	175	11.34	STJ	1000	950	907	870	836	389	350	320	294	272	⊕	-1.5	-5.6	-12.7	4
6	S45SJT1	45 AUTO	205	13.28	STJ	970	926	887	853	821	428	390	358	331	307	⊕	-1.6	-6	-13.4	5

American Eagle® Handgun

USAGE	FEDERAL LOAD NO.	CALIBER	BULLET WEIGHT IN		BULLET STYLE	VELOCITY IN FEET PER SECOND (TO NEAREST 10 FPS)					ENERGY IN FOOT-POUNDS (TO NEAREST 5 FOOT-POUNDS)					TRAJECTORY SIGHTS .9 INCHES ABOVE BORE LINE				TEST BARREL LENGTH INCHES
			GRAINS	GRAMS		MUZZLE	25 YDS.	50 YDS.	75 YDS.	100 YDS.	MUZZLE	25 YDS.	50 YDS.	75 YDS.	100 YDS.	25 YDS.	50 YDS.	75 YDS.	100 YDS.	
AMERICAN EAGLE																				
5	AE5728A	5.7X28	40	2.59	TMJ	1655	1514	1387	1275	1179	243	204	171	144	124	⊕	0.0	-1.2	-3.8	4.8
5	AE25AP	25 AUTO	50	3.24	FMJ	760	738	717	697	677	64	60	57	54	51	⊕	-3.1	-10.4	-22.1	2
5	AE32AP	32 AUTO	71	4.6	FMJ	900	872	846	821	798	128	120	113	106	100	⊕	-2.0	-7.0	-15.2	4
5	AE327A	327 FEDERAL MAGNUM	85	5.51	JSP	1400	1306	1221	1150	1091	370	322	281	250	225	⊕	-0.4	-2.2	-5.7	4-V
6	AE327	327 FEDERAL MAGNUM	100	6.48	JSP	1500	1408	1324	1248	1181	500	440	389	346	310	⊕	-0.2	-1.6	-4.5	4-V
5	AE380AP	380 AUTO	95	6.16	FMJ	980	937	899	865	835	203	185	170	158	147	⊕	-1.6	-5.8	-13.0	3.75
5	AE9DP	9MM LUGER	115	7.45	FMJ	1180	1106	1048	1001	961	356	312	280	256	236	⊕	-0.9	-3.7	-8.7	4
5	AE9AP	9MM LUGER	124	8.04	FMJ	1150	1095	1049	1010	977	364	330	303	281	263	⊕	-0.9	-3.8	-8.8	4
5	AE9FP	9MM LUGER	147	9.53	FMJ FP	1000	976	953	933	914	326	311	297	284	273	⊕	-1.4	-5.2	-11.5	4
5	AE38S3	38 SUPER +P	115	7.45	JHP	1130	1067	1016	974	938	326	290	264	242	225	⊕	-1.0	-4.1	-9.5	5
5	AE357S2	357 SIG	125	8.1	FMJ	1350	1266	1192	1130	1078	506	445	395	354	323	⊕	-0.5	-2.4	-6.1	4
5	AE38K	38 SPECIAL	130	8.42	FMJ	890	870	852	834	817	229	219	209	201	193	⊕	-2.0	-7.0	-15.1	4-V
5	AE38B	38 SPECIAL	158	10.24	LRN	770	758	745	733	722	208	201	195	189	183	⊕	-2.9	-9.8	-20.7	4-V
5	AE357A	357 MAGNUM	158	10.24	JSP	1240	1187	1139	1098	1063	539	494	455	423	396	⊕	-0.6	-3.0	-7.1	4-V
5	AE40R2	40 S&W	155	10.04	FMJ	1160	1095	1043	1000	963	463	413	374	344	319	⊕	-0.9	-3.8	-8.9	4
5	AE40R3	40 S&W	165	10.69	FMJ	1130	1078	1035	999	967	468	426	392	365	342	⊕	-1.0	-4.0	-9.1	4
5	AE40R1	40 S&W	180	11.66	FMJ	1000	972	946	923	901	400	377	358	340	324	⊕	-1.4	-5.3	-11.6	4
5	AE10A	10MM AUTO	180	11.66	FMJ	1030	998	970	945	921	424	398	376	357	339	⊕	-1.3	-4.9	-10.9	5
5	AE44A	44 REM. MAGNUM	240	15.55	JHP	1230	1169	1117	1073	1035	806	729	665	613	571	⊕	-0.7	-3.1	-7.4	4-V
5	AE44B	44 REM. MAGNUM	240	15.55	JSP	1270	1204	1146	1098	1056	859	772	700	642	595	⊕	-0.6	-2.9	-6.9	4-V
5	AE45A	45 AUTO	230	14.9	FMJ	890	872	856	840	824	404	389	374	360	347	⊕	-2.0	-6.9	-15.0	5
5	AE45LC	45 COLT	225	14.58	JSP	860	844	828	813	799	369	356	343	330	319	⊕	-2.2	-7.5	-16.1	4
AMERICAN EAGLE SUPPRESSOR																				
5	AE9SUP1	9MM LUGER	124	8.04	FMJ	1030	996	966	940	915	292	273	257	243	231	⊕	-1.3	-4.9	-11.0	4
5	AE45SUP1	45 AUTO	230	14.9	FMJ	840	821	803	785	769	360	344	329	315	302	⊕	-2.3	-8.0	-17.2	5
AMERICAN EAGLE IRT																				
5	AE9N1	9MM LUGER	124	8.04	TMJ	1120	1070	1028	993	961	345	315	291	271	255	⊕	-1.0	-4.0	-9.3	4
5	AE9N2	9MM LUGER	147	9.53	TMJ	1000	976	953	933	914	326	311	297	284	273	⊕	-1.4	-5.2	-11.5	4
5	AE40N1	40 S&W	180	11.66	TMJ	1000	972	946	923	901	400	377	358	340	324	⊕	-1.4	-5.3	-11.6	4
5	AE45N1	45 AUTO	230	14.9	TMJ	850	834	819	804	790	369	355	343	330	319	⊕	-2.2	-7.7	-16.4	5

Fusion® Handgun

USAGE	FEDERAL LOAD NO.	CALIBER	BULLET WEIGHT IN		BULLET STYLE	VELOCITY IN FEET PER SECOND (TO NEAREST 10 FPS)					ENERGY IN FOOT-POUNDS (TO NEAREST 5 FOOT-POUNDS)					TRAJECTORY SIGHTS .9 INCHES ABOVE BORE LINE				TEST BARREL LENGTH INCHES
			GRAINS	GRAMS		MUZZLE	25 YDS.	50 YDS.	75 YDS.	100 YDS.	MUZZLE	25 YDS.	50 YDS.	75 YDS.	100 YDS.	25 YDS.	50 YDS.	75 YDS.	100 YDS.	
FUSION																				
2	F357FS1	357 MAGNUM	158	10.24	FUSION SP	1240	1187	1139	1098	1063	539	494	455	423	396	⊕	-0.6	-3.0	-7.1	4-V
2	F10FS1	10MM AUTO	200	12.96	FUSION SP	1200	1147	1102	1063	1030	639	585	539	502	471	⊕	-0.8	-3.3	-7.7	5
2	F41FS1	41 REM. MAGNUM	210	13.61	FUSION SP	1230	1172	1122	1079	1043	705	641	587	543	507	⊕	-0.7	-3.1	-7.3	4-V
2	F44FS1	44 REM. MAGNUM	240	15.55	FUSION SP	1290	1221	1162	1110	1067	887	795	719	657	607	⊕	-0.6	-2.7	-6.7	4-V
2	F454FS1	454 CASULL	260	16.85	FUSION SP	1350	1266	1192	1130	1078	1052	925	821	737	671	⊕	-0.5	-2.4	-6.1	5.7-V
2	F460FS1	460 S&W	260	16.85	FUSION SP	1600	1495	1397	1309	1229	1478	1289	1126	989	872	⊕	-0.1	-1.3	-3.7	8.4-V
2	F500FS2	500 S&W	325	21.06	FUSION SP	1450	1357	1272	1198	1134	1517	1329	1168	1035	929	⊕	-0.3	-1.9	-5.0	8.4-V
2	F50AEFS1	50 ACTION EXPRESS	300	19.44	FUSION SP	1550	1451	1361	1278	1205	1600	1402	1233	1088	967	⊕	-0.1	-1.5	-4.1	6